



product



Specification

MP 003

Contract Grade Multi Purpose Flooring Adhesive



MP003 is the installer's choice for price and performance.

- Longer Working Time for Carpet or Vinyl
- Non-Staining for Felt-Backed Vinyl Sheet Goods
- Strong Early Grab
- Easy to Trowel

Description: MP 003 Contract Grade Multi Purpose Flooring Adhesive

Flammability: Non-Flammable

Open Time: 15 minutes

Working Time: 45-60 Minutes

Clean Up: Water when wet; Safety solvent or mineral spirits when dry.

Shelf Life: One year in closed container.

Limitations: Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F for 24 hours and stir before using. For interior use only.

Packaging: 4 Gallon • 1 Gallon • 1 Quart

For The Installation Of:

- Jute Backed Carpet • Urethane • ActionBac® Carpet
- Light Latex Unitary Carpet • Felt-backed Sheet Vinyl

For Use Over:

- Concrete • Plywood • APA Grade Particle Board • OSB • Terrazzo • Hardwood Floors • Latex-Portland Cement Underlayment • Gypsum Cement Underlayment • VCT • Felt Backed Vinyl Sheet Goods (prime

with an acrylic sealer, such as Capitol's LL400 Liquid Latex) • Do not use over existing cutback





Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the correct trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for 15 minutes prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 45 minutes.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturer's recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

Caution:

Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. KEEP OUT OF REACH OF CHILDREN

Trowel Requirements

 <p>1/16 x 1/16 x 1/16</p> <p>18-19 square yards /gallon • Felt Back Vinyl sheet</p>	 <p>3/32 x 3/32 x 3/32 "V"</p> <p>17-18 square yards /gallon • Jute • Low Density Urethane</p>
 <p>1/8 x 1/8 x 1/16 "V"</p> <p>13-14 square yards /gallon • ActionBac® / Jute</p>	 <p>1/8 x 1/8 x 1/8</p> <p>8-9 square yards /gallon • Light Latex Unitary</p>



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722

800-831-8381 • Fax: 706-277-5753

Jim Walker ProSeries TechLine 888-234-8400

Website www.capitolusa.com

MP 003

Contract Grade Multi Purpose Flooring Adhesive

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: Capitol USA, LLC
Address: 300 Cross Plains Blvd.
PO Box 20203 • Dalton, GA 30722
Telephone #: 1-800-831-8381
Emergency Phone: 800-535-5053
Generic ID: Latex Based Flooring Adhesive
DOT Hazard Classification: None
Product Identity: MP003 Contract Grade
Multi Purpose Flooring Adhesive

SECTION II - HAZARDOUS COMPONENTS

None per OSHA Regulation: 29CFR1910.1200
None per SARA Title III, Section 313 and
TSCA 40 CRF 372

SECTION III - PHYSICAL DATA

Initial Boiling Point: 212°F. Vapor Pressure:
Same as water. Vapor Density (Air=1.0): Same
as water. Specific Gravity: 1.22. G/L VOC
(calculated): 0.00. Percent Volatiles: 32.0%.

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point: 200°F. Explosive Limit (Product):
NA. Extinguishing Media: None to avoid.
Hazardous Decomposition Products: Carbon
monoxide, carbon dioxide, oxides of nitrogen
and sulfur. Special Fire Fighting Procedures:
Wear self-contained breathing apparatus.
Unusual Fire & Explosion Hazards: None

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: NA. Threshold
Limit Value: NA. Effects of Exposure: Eyes-
Possible mild irritation. Skin - Possible mild
irritation. Breathing - None known.

SECTION VI - REACTIVITY DATA

Stability: Stable. Incompatibility: None.
Hazardous Decomposition: None. Hazardous
Polymerization: None. Conditions To Avoid:
None Known.

SECTION VII - SPILL OR LEAK PROCEDURES

Absorb liquid on paper, vermiculite, floor
absorbent, or other absorbent material.
Solidified materials accepted for landfill
disposal in most locations. Check all local,
state, and federal regulations.

SECTION VIII - PROTECTIVE EQUIPMENT

Ventilation: Open all available windows and
entrances to insure good ventilation.
Respirator Protection: None needed.
Protective Gloves: If sensitive. Eye Protection:
Wear glasses or protective goggles to avoid
splashes. Other Protective Equipment: None
required. Wash Hands Thoroughly with Soap
and Water.

SECTION IX - SPECIAL PRECAUTIONS

Protect from freezing. Use only in
applications as stated on the label. Do not
take internally. Close container after each use.
Avoid skin and eye contact.

Capitol USA believes the data set forth herein
is accurate as of the date hereof, and makes no
warranty with respect thereto and expressly
disclaims all liability for reliance thereon.
Such data are offered solely for your
consideration, investigation and verification.



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com